




Standard
Module

BIPV

Solar
Car Sunroof



Standard Module

GSM6 Series 6" Cell Module (200, 205, 210 Wp)

Features

- 54 presorted high efficient multi-crystalline silicon solar cells
- Long term stability by quality control and exact tuning of components
- Strict power measurement that minimizes the power tolerance to +/-3%
- Sorting limit of module classification to +/-2.5W

Modules are manufactured in ISO 9001 and 14001 certificated facilities to guarantee prime quality as well as environment-friendly products

IEC certificate

The test sequence of the IEC 61215 and IEC 61730 confirm that Gloria Solar modules are capable of withstanding the artificial loads of the materials as well as safety qualification. It provides reliable performance and safety for entire range of Gloria Solar modules

REACH certificate

REACH Regulation (EC) No 1907/2006:

Article 7 - Registration and notification of substances in articles

Article 33 - Duty to communicate information on substances in articles

Dimensions

Length * Width (mm)	1494*992
Thickness (mm)	50
Weight (kg)	18



Standard Module

GLORIA SOLAR CO., LTD.

5th Floor, Building C, No. 3, Nanke 7th Rd., Sinshih Township,
Tainan county 741 Taiwan, R.O.C.
Tel: +886-6-5059500
Fax: +886-6-5057100
http://www.gloriasolar.com
e-mail: service@gloriasolar.com

GSM6 Series 6" Cell Modules

Electrical characteristics under standard test condition (STC) ¹

		GSM6-200B-E1	GSM6-205B-E1	GSM6-210B-E1
Typical power (P _{max}) ²	W	200	205	210
Voltage at typical power (V _{mp})	V	25.4	25.9	26.4
Current at typical power (I _{mp})	A	7.88	7.92	7.97
Open circuit voltage (V _{oc})	V	32.7	32.9	33.0
Short circuit current (I _{sc})	A	7.94	8.00	8.07
Module Efficiency	%	13.49	13.83	14.17

1. STC : AM1.5G, 1000W /m², cell temperature of 25 °C .

2. Power tolerance at maximum power under STC condition = ±3%

Temperature coefficient

Temperature coefficient current	α	Ts(Isc)	0.0254%/K
Temperature coefficient voltage	β	Tc(Voc)	-0.3003%/K
Peak power temperature coefficient	γ	Tc(Pmax)	-0.4147%/K

Performance at low irradiance

** Module efficiency at 200 W/m², 25C is lower than that at STC by approximately 6.3% (relative)

System Integration

** Maximum system voltage= 1000 V

** Fuse rating : 15 A

Front View

Side View

Back View

